

KEEP OUT OF REACH OF CHILDREN

WARNING

PRECAUTIONARY STATEMENTS: Avoid breathing. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well ventilated area. Protect from sunlight. Store in a well ventilated area. Dispose of contents/container per applicable regulations.

IF EYE CONTACT: Flush with large amounts of cool water for at Least 15 minutes while holding upper and lower eye lids open. Call your physician.

IF SWALLOWED: Do not induce vomiting. Contact a physician immediately.

IF SKIN CONTACT: Wash with clean soapy water and rinse.

CONTENTS: Vinyl Acrylic Resin, Non-Hazardous, less than 40% Proprietary Mixed Acids and Less than 5% Non-Hazardous



Quik Tann

RUST ELIMINATOR AND PRIMER

Halts Existing Rust and Prevents
Future Corrosion



**Chemically Converts Rusted Surfaces into
Paintable Primed Surfaces
No Need for Sandblasting,
Heavy Grinding or Needed**



New Wt. Quart (32 oz.)

DIRECTIONS FOR USE

Shake Well Before Use

Clean area to remove any loose debris, (flaking, chips, etc.)

Spray, Brush or Roller Quik Tann liberally. (Average usage is one gallon of Quik Tann to 500 square feet of surface area, less for cleaner surface rust, more for extreme rusted surfaces.

Quik Tann will dry within 30 to 60 minutes, depending on humidity conditions.

Quik Tann surface conditioner and primer changes rust into a dark protective polymeric coating. It chemically converts existing rust to an inert coating that seals air moisture and prevents against future corrosion.

Quik Tann provides an excellent primer coating for application of quality paints. Surfaces protected with this primer and other quality coatings will resist the effects of weather, rain, sun, and salt spray without peeling or cracking.



Where Corrosion Meets Solutions